

Private Enterprise

79035, Ukraine, Lviv, Zelena str., h.97, of.12 c\a 26006051813983 in PC CB «PrivateBank», MFI 335496, USREOU 22023208 INN 220232005265, tel./fax N_2 0 (32) 270 – 45 – 48

Competence And Rationality!

r.n. 10/05/3 from 10/05/2019 y

Equipment for mixing and dissolving liquids in the stream USJ-01M.





Equipment is used for mixing and dissolving liquids in the flow of the USJ-01M type, mixing in the stream from two to six separate components, in particular low-octane gasoline with VKD additives.

Equipment for serial production of automobile gasolines and diesel fuels of the USJ-01M is manufactured in Ukraine according to TU.U.13931214.007-99, matches the requirements of standards and has all the necessary approvals for use including:

- resolution № 160.00.53.29.53.1 from 17.07.2000 from Territorial Administration of the State Labor Protection Service;
- conclusion of the State Administration of Ecology and Natural Resources № 03-06/2427 from 10.10.2000;
- hygienic conclusion of the State Sanitary and Epidemiological Expertise № 03-05/1068 от 19.03.2001

Equipment is exploited indoors and outdoors under a canopy.

№	Technical charecteristics	USJ-01M
	Number of mixible liquids	2 - 6
	Capacity of the mixer for the main liquid (water), m ³ / h, not less than	11 - 12
	The amount of additives in the mixture obtained %, not more than Quantity of liquid to be weighed, m ³ / h,	45
	■ 1stindicator	1 - 7*
	■ 2dindicator	0,2 - 1,0*
	■ 3dindicator	0,5 - 3,5*
	■ 4sindicator	0,5 - 3,5*
	■ 5sindicator, l/h	14 - 32*
	The visual installation of the consumption of components by the indicator changes the density of the mixture gasoline on,%	1,4
	Installed power, kW, not more than	15
	Primary fluid injection pressure, MPa The work of the CENNBS pump - under the gulf	0,9 - 1,0
	Height of the mixture, m, max Overall dimensions, mm, not more than:	10
	Equipment: length / width / height	1380 / 900 / 750
	Pump with trap: length / width / height Weight, kg, not more than:	1100 / 500 / 600
	Equipment	95
	Pump with trap iven while using one indicator. Indicator usage is indicated when the equipment is running on v	250

-We develop emulsion for mulations and supply chemical components for their production